

Amended ~~New~~ claims

1. (independent) A fish cage comprising the features of:

~~a)~~ an egg-shaped shell (1) with a generally vertical long axis and gradually narrowing shape towards its tip volume portion (4);

~~b)~~ said shell (1) forming a generally rigid tank;

~~c)~~ said shell (1) being closed,

~~d)~~ said shell (1) having one or more water inlets (11),

~~e)~~ said shell (2) having one or more water outlets (16, 29),

characterized in that

- said egg-shaped tank (1) is arranged for holding a water volume in its major lower volume portion and enclosing air in its minor, upper tip volume portion (4);

- an axial oriented central tube (2) extending from the upper tip portion (4) of the egg-shaped shell (1) to the lower, wider end of said egg-shaped shell (1);

- a vertical axially running folding fish grid (23) comprising a water-permeable central frame (23a) with running wheels for running on said central tube (2), said fish grid having, ~~said~~ folding wings (23b) arranged for folding in towards said central tube (12) and further arranged for folding out with their outer ends arranged for following the inner surface of said egg-shaped shell (1).

~~25.~~ The fish cage of any of the preceding claims claim 1, comprising

~~- a fixed ballast (7) in the broader, lower end of said egg-shaped shell (1).~~

Kommentert [PRF1]: Ballast:

32. The fish cage of claim 1, comprising

- a ring-shaped buoyancy collar (3, 24) mounted on said egg-shaped shell (1).

43. The fish cage of claim 2, said ring-shaped buoyancy collar (3) arranged near said tip portion (4), for holding said egg-shaped shell (1) in a semi-submerged position with said tip portion extending above the sea surface (~~20~~).

Kommentert [PRF2]: semi-submersible:

54. The fish cage of claim 2, said ring-shaped buoyancy collar (24) arranged near a widest "equatorial" position of said egg-shaped shell (1), said ring-shaped buoyancy collar (24) further having a ring-shaped water ballast tank (25) for submerging said egg-shaped shell (1) with its tip portion (4) below the sea surface (~~20~~).

Kommentert [PRF3]: submersible:

~~5.~~ The fish cage of any of the preceding claims, comprising

~~a fixed ballast (7) in the broader, lower end of said egg-shaped shell (1).~~

Kommentert [PRF4]: Ballast just moved up to 2. place

67. The fish cage of any of the preceding claims, comprising

- said at least one water inlets (11, 12) arranged in the lower portion of the egg-shaped shell (1),
- said water outlet (16, 29) near below an internal water surface level of the egg-shaped shell (1),

so as for allowing bottom to top or "~~reverse~~" circulation of water through the egg-shaped shell (1) while maintaining said air volume in said tip (4).

Kommentert [PRF5]: Water circulation

78. The fish cage of any of the preceding claims, comprising

- a passage (18, 30) near the perimeter (17) of the internal water surface, to a circular holding tank (19, 32) for sludge, non-eaten fodder, fish excrements, and provided with a drain for excess water.

Kommentert [PRF6]: Sludge drain:

89. The fish cage of claim **67** or **78**, wherein said water inlet (11) is horizontal and tangentially directed into the water within said egg-shaped shell (1).

Kommentert [PRF7]: Tangential water inlet

910. The fish cage of claim **2**, **67**, **87** or **98**, wherein

- said water inlets (11) are arranged just above said fixed ballast (7).

1011. The fish cage of any of claims **67** - **910**, comprising

- a lower inlet pump (12) arranged at the lower end of said central tube (2).

Kommentert [PRF8]: Lower water inlet in tube

1112. The fish cage of claim 11, comprising

- at least one water inlet (13, 14, 15) arranged through the side wall of said central tube (2) to within the water volume of said shell (12).

12. The fish cage of claim 1,

~~- said fish grid's folding wings (23b) having guiding wheels (23g) at their outer ends.~~

~~13. The fish cage of claim 6, comprising~~

~~a vertical axially running folding fish grid (23) comprising a water permeable central frame (23a) with running wheels for running on said central tube (2), said fish grid having folding wings (23b), preferably with guiding wheels (23g) at their outer ends, said folding wings (23b) arranged for folding in towards said central tube (12) and further arranged for folding out with their outer ends arranged for following the inner surface of~~

Kommentert [PRF9]: This is the remainder of claim 13 (now claim 12) not included in claim 1, "preferably with guiding wheels ...", which is not obligatory in claim 13, but a dependent option.

This claim is now not dependent of claim 6, because claim 6 has been included in claim 1.

~~said egg-shaped shell (1).~~

~~13~~¹⁴. The fish cage of claim ~~1~~¹³,

- said folding fish grid (23) arranged for being stored in a folded-in position within the air above the internal water surface level, within said upper tip portion (4),
- said folded fish grid (23) arranged for being lowered to a position below the internal water surface in the egg-shaped shell (1);
- said fish grid (23) arranged for being unfolded for the folding wings (23b) to engage with the inner surface of the egg-shaped shell (1);
- said unfolded fish grid (23) arranged for being elevated to force part of all of the fish above said fish grid (23) to move upwardly toward the upper tip portion (~~4~~).

Kommentert [PRF10]: Use of the folding grid

This claim is no longer dependent on claim 13, but dependent on claim 1 where 13 has been included.

~~14~~¹⁵. The fish cage of claim ~~12~~¹³ or ~~13~~¹⁴, comprising

- ellipsoid grid bars (23e), (23f) in said fish grid (23) arranged for being rotated between a closed position impenetrable for fish, to a partly or fully open position wherein fish below a given grating size may pass said fish grid (23).

~~15~~¹⁶. The fish cage of any of the preceding claims ~~16~~ - ~~14~~¹⁵, comprising

- a vertical mooring line (26) arranged from extending from a hydraulic cylinder or winch (28) within said axial oriented central tube (12) near the upper tip portion (4) and downwardly through the lower end of said central tube (12) to an anchor below the egg-shaped shell (~~1~~).

Kommentert [PRF11]: Mooring line

This claim was dependent on claim 6 which was included in claim 1, thus this renumbering.

~~16~~¹⁷. The fish cage of any of the preceding claims, comprising

- an air valve (27) arranged above the internal water level in the air volume within said tip (4), so as for letting out air in order to reduce the floatability of the egg when going to submergence.

~~17~~¹⁸. The fish cage of claim ~~16~~¹⁷, wherein

- said air valve (27) is arranged at the upper allowable internal water level within said otherwise air-filled tip (4).

~~18~~¹⁹. The fish rearing tank of claim ~~17~~¹⁸, comprising a ventilation fan in said air-filled tip (4) that also regulates adequate air intake.

~~19~~¹⁹. The fish cage of any of the preceding claims, wherein

- feeding pipes (21) are arranged from above the internal water surface, within the central tube (12) and having an exit (22) below water from the central tube (12),

- an air driven piston at the top of the feeding pipes, arranged for moving downwardly after the pellet fodder has been fed into the pipe, to push fodder out of the lower opening (22) to provide fish with a batch of fodder.

21. The fish rearing tank of any of the preceding claims, said shell (1) being seamless.

~~20~~22. The fish cage of any of the preceding claims, wherein said egg-shaped shell (1) generally has a double wall. ~~(see Fig. 5D).~~

Kommentert [PRF12]: (see Fig. 5D).

23. The fish rearing tank of any of the preceding claims, the volume of said egg-shaped shell (1) being between 4500 m³ and 22000 m³ or more.

24. The fish rearing tank of any of the preceding claims, the diameter of the intake pipe being 2250 mm.

25. The fish rearing tank of any of the preceding claims, the water discharge module (16, 29) directed with an outlet direction along with the water rotation generated by the inlet direction of the tangential water inlets (11).

26. A method of rearing fish, comprising the steps of:

Kommentert [PRF13]: METHOD CLAIMS

- providing a fish rearing tank comprising the features of:

~~a)~~ an egg-shaped shell (1) with a generally vertical long axis and gradually narrowing shape towards its tip volume portion (4);

~~b)~~ said shell (1) forming a generally rigid tank;

~~c)~~ said shell (1) being closed,

~~d)~~ said shell (1) having one or more water inlets (11),

~~e)~~ said shell (2) having one or more water outlets (16, 29),

said egg-shaped tank (1) for holding a water volume in its major lower volume portion and enclosing air in its minor, upper tip volume portion (4);

characterized by

- a vertical axially running, folding fish grid (23) comprising a water-permeable central grating frame (23a) with running wheels for running on a vertical axial central tube (2) extending from said tip (4) to the wider bottom, said fish grid (23) having folding wings (23b), preferably with guiding wheels (23g) at their outer ends, said folding wings (23b) arranged for folding in towards said central tube (12) and further arranged for folding out with their outer ends arranged for following the inner surface of said egg-shaped shell (1);

characterized by

- placing a number of fish in said egg-shaped shell (1);
 - circulating in fresh seawater through said water inlets (11, 12) arranged in the lower portion of the egg-shaped shell (1), ~~and~~
 - circulating out used water through said water outlet (16, 29) near below an internal water surface level of the egg-shaped shell (1),
- so as for conducting bottom to top or "~~reverse~~"-circulation of water through the egg-shaped shell (1) while maintaining its air-filled volume in said tip (4), and
- for moving all or part of the fish within the shell (1);
 - running said folded grating frame (23a) to the lower end of said egg-shaped shell (1);
 - unfolding said grating frame (23a) for said folding wings (23b) to reside with their outer ends near or at said inner surface of said egg-shaped shell (1);
 - adjusting the grating so as for enabling sorting or moving a part or all of the contained fish population;
 - running said grating frame (23a) upwardly while said folding wings follow said inner surface of said egg-shaped shell (1) thereby sorting or moving said part of the contained fish.

2726. The method of claim 2625, opening an air valve (27) to let out part of the air contained in said tip (4), and allowing the tip (4) to submerge to a desired depth below the sea surface, while conducting the circulation of water through the shell (1).

2827. The method of claim 2625 or 2726, controlling the water content in a ballast tank (25) about said shell (1), and allowing the tip (4) to submerge to a desired depth below the sea surface, while conducting the circulation of water through the shell (1).

2928. The method of claim 2625, 2726, or 2827, tightening a mooring line (26), and allowing the tip (4) to submerge to a desired depth below the sea surface, while conducting the circulation of water through the shell (1).

~~3029. The method of any of the preceding claims, for moving all or part of the fish within the shell (1);~~
~~—providing a vertical axially running, folding fish grid (23) comprising a water permeable central grating frame (23a) with running wheels for running on said central tube (2), said fish grid having folding wings (23b), preferably with guiding wheels (23g) at their outer ends, said folding wings (23b) arranged for folding in towards said central tube (12) and~~

~~further arranged for folding out with their outer ends arranged for following the inner surface of said egg-shaped shell (1);
—running said folded grating frame (23a) to the lower end of said egg-shaped shell (1);
—unfolding said grating frame (23a) for said folding wings (23b) to reside with their outer ends near or at said inner surface of said egg-shaped shell (1);
—adjusting the grating so as for enabling sorting or moving a part or all of the contained fish population;
—running said grating frame (23a) upwardly while said folding wings follow said inner surface of said egg-shaped shell (1) thereby sorting or moving said part of the contained fish.~~

30. The method of claim ~~26~~²⁹, folding in said folding wings (23b) and running said central grating frame (23a) to above the water surface for internal storage while not in use for grating.

31. The method of any of the preceding claims ~~26 - 30~~, pumping in water tangentially through said water inlets (11) near the lower end of said shell (1) so as for generating a rotational and upward water movement through said shell (1) to said water discharge modules (16, 29) near below the internal water surface.

32. The method of claim 31, allowing said rotational and upward water movement about said central axial tube (2).

33. The method of claim 32, due to the rotational rising water movement, allowing particles to concentrate at the internal water surface towards the perimeter of the tank (17), and letting out said surface particles to move out over the passage (30) to said sludge holding tank (32).

34. The method of any of the preceding claims ~~26 - 33~~, loading feed into one or more feeding pipes (21) mounted inside the centre tube (2) and extending between 3 meters above water level and end approximately 5 and 10 meters above the bottom of the tank at which point they exit the tube into the tank (22), driving an air driven piston downwardly after the filling with desired volume of feed into the pipe, pushing the feed downwards and out of the lower opening (22) of the pipe providing fish with batches of feed.